MEMOR™ 10



OIDOJATACOGIC

MEMOR™ 10 – A MOBILE COMPUTER DESIGNED FOR ENTERPRISE

If you are looking for the power and the performance of a mobile computer but are concerned about the typical Enterprise challenges, the Datalogic Memor 10 PDA is the perfect rugged device for you!

Memor 10 incorporates the latest mobile computer technologies and the user friendly experience of Android[™] in a slim and compact design, combined with high performance 1D/2D bar code scanning and industrial robustness for almost any indoor or outdoor environment.

TOP PERFORMANCE

The Memor 10 is powered by a superior octa-core platform clocked at 2 GHz for top performance for the most demanding applications, and features Android 9 (upgradeable to Android 10) with Google Mobile Services (GMS).

Moreover, the Memor 10 is one of the first rugged mobile computers to be validated by Google for the 'Android Enterprise Recommended' program for rugged devices.

WIRELESS CHARGING MEETS SWAPPABLE BATTERY

The Memor 10 incorporates Datalogic's industry-first wireless charging system for ultra-reliable contactless charging, thus eliminating the need for cleaning contacts on the device and docks. Moreover, Memor 10 offers a 1-piece swappable battery for the best operational advantage.

COMMUNICATIONS

GREEN

The Memor 10 leverages a complete set of embedded wireless technologies for both indoor and outdoor applications: dual band Wi-Fi including the latest 802.11ac standard, Bluetooth® v5 with BLE for fast and ultra-low power connections, NFC for easy pairing, and particularly the cellular area voice and data connectivity, already leveraging the next generation of LTE-Advanced/4G+.

android enterprise recommended

FEATURES

- Ultra-Ergonomic, compact and robust
- 5 inch capacitive multi-touch HD display with Dragontrail™ hardened glass
- Android 9 with Google Mobile Services (upgradeable to Android 10)
- · Wireless charging eliminates all contacts on the device and cradle
- Ruggedized with drop resistance to 1.5 m / 5 ft to concrete and IP65 sealing
- Dual band Wi-Fi including the latest 802.11ac standard and 802.11r/k for fast roaming
- Full suite of cellular connectivity for voice and data, featuring LTE-Advanced / 4G+
- Assisted GPS for location based apps
- Bluetooth v5 short range wireless technology
- NFC for proximity communications
- Advanced 2D ultra-slim imager with Datalogic's distinctive 'Green Spot' technology for visual good-read feedback; Megapixel imager
- Datalogic's SoftSpot[™] technology for innovative triggering through the touch display
- Chemical resistant plastics / enclosure designed to withstand daily cleaning with harsh disinfectant solutions
- EASEOFCARE Service Plans offer a wide range of options to protect your investment, ensuring maximum productivity and ROI. Datalogic Shield, for Android security patches and OS upgrades, is included with EASEOFCARE.





INDUSTRY - APPLICATIONS

- Retail:
 - Assisted sales
 - Inventory
 - Access control
 - Shop floor applications
 - Mobile POS
- T&L:
 - Route accounting
 - Direct store delivery
 - Workforce management
 - Courier value-added services
- Manufacturing:
 - Production and quality control
 - Intra-logistics
 - Inventory
 - Field maintenance
- Healthcare:
 - Bedside carePharmacy
 - Filaillacy
 - Inventory managementLabs
 - Home healthcare

NOTE: The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

MEMOR™ 10 **TECHNICAL SPECIFICATIONS**

WIRELESS COMMUNICATIONS	
Local Area Network (WLAN)	IEEE 802.11 a/b/g/n/ac and 802.11 k/r/v; Frequency range: Country dependent, typically 2.4 GHz and 5 GHz bands
Personal Area Network (WPAN)	Bluetooth wireless technology v5 (A9 version) / v4.2 (A8 version), Classic Bluetooth and BLE
NFC Communication	Support for the following standards: ISO14443-4 (type-A, type-B); ISO15693; Mifare; Felica
WWAN / Cellular	LTE-Advanced / 4G+; Cat 6 • EMEA and ROW Configuration: GSM: Quad band; CDMA: BC0; WCDMA: B1/5/8; FDD_LTE:B1/3/5/7/8/20/28; TDD_LTE:B38/39/40/41 • North America Configuration (PTCRB certified): GSM: Quad band; CDMA: BC0/1; WCDMA: B1/2/4/5/8; FDD_LTE:B2/4/5/7/12/13/17/25/26; TDD_LTE:B38/39/40/41
Global Positioning System (GPS)	Integrated Assisted-GPS (A-GPS) Supported Types: GPS, GLONASS, BeiDou
DECODING CAPABILITY	
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
Digital Watermark Codes	Digimarc® Barcode
2D Codes	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, Dotcode
Postal Codes	Australian Post, Japan Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC), UPU FICS, USPS Intelligent Mail
Stacked Codes	Micro-PDF417, PDF417, GS1 DataBar Composites, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional
ELECTRICAL	
Battery	Replaceable battery pack with rechargeable Li-Ion batteries; 3.8v; 4,100 mAh (15.6 Watt-hours)
Battery Wireless Charging	
	Li-Ion batteries; 3.8v; 4,100 mAh (15.6 Watt-hours)
Wireless Charging	Li-Ion batteries; 3.8v; 4,100 mAh (15.6 Watt-hours)
Wireless Charging ENVIRONMENTAL	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD
Wireless Charging ENVIRONMENTAL Drop Resistance	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65
Wireless Charging ENVIRONMENTAL Drop Resistance Tumbles	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot
Wireless Charging ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant
Wireless Charging ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant (both Standard and Healthcare models) Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach;
Wireless Charging ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant (both Standard and Healthcare models) Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F
Wireless Charging ENVIRONMENTAL Drop Resistance Jumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant (both Standard and Healthcare models) Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F
Wireless Charging ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant (both Standard and Healthcare models) Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F
Wireless Charging ENVIRONMENTAL Drop Resistance Jumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant (both Standard and Healthcare models) Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F
Wireless Charging ENVIRONMENTAL Drop Resistance Jumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces SENSORS	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant (both Standard and Healthcare models) Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F USB-C: High Speed USB 2.0 Host and Client
Wireless Charging ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces SENSORS Vibration	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant (both Standard and Healthcare models) Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F USB-C: High Speed USB 2.0 Host and Client Software programmable for duration and intensity
Wireless Charging ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces SENSORS Vibration Accelerometer	Li-lon batteries; 3.8v; 4,100 mAh (15.6 Watt-hours) Qi Compliant; 10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test. Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot IP65 Chemical cleanser and industrial oil resistant (both Standard and Healthcare models) Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F USB-C: High Speed USB 2.0 Host and Client Software programmable for duration and intensity 3-Axis accelerometer to detect orientation

PHYSICAL CHARAC	TERISTICS	
Dimensions	15.5 x 7.8 x 1.87 cm / 6.1 x 3.07 x 0.73 in	
Display	5 inch IPS HD resolution 720 x 1280; LED backlight; Touch Screen: 5 points multi-touch capacitive panel with Dragontrail hardened glass	
Keys	Physical Keys: 2 side scan keys; Power On/Off; Volume Up/ Down; 3 user programmable Android™ keys	
Weight	With Battery: 285.0 g / 10.0 oz	
READING PERFORMANCE		
Camera	Resolution: 13 megapixel; Illumination: User controllable LED flash; Lens: Auto focus	
Scan Engine	2D Ultra slim area imager (supports 1D / 2D codes); Datalogic's 'Green Spot' for good-read feedback; Halogen™ DE2102 scan engine: Depth of Field: 4 to 90 cm / 1.6 to 35 in depending on bar code density and type; Resolution: Megapixel (1280 x 800 pixels); Illumination: White and Red LEDs (for Digimarc); Aiming: 650nm VLD; Field of View: 42°H x 26°V	
Print Contrast (Minimum)	25%	
Minimum Element Width	Halogen™ DE2102 scan engine: 1D Linear: 0.0635 mm / 2.5 mils; PDF: 0.0762 mm / 3 mils; Data Matrix: 0.152 mm / 6 mils	
SAFETY & REGULA	TORY	
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.	
Environmental Compliance	Complies to EU RoHS	
SOFTWARE		
Applications	Datalogic's SoftSpot technology for configurable soft triggers; Supports Datalogic's Queue Busting app; Pre-licensed device and browser lockdown powered by 42Gears; Enterprise class PTT available from Zello	
Provisioning	Android Zero-Touch, QR Code enrollment, NFC Bump provisioning	
Configuration and Maintenance	Scan2Deploy Studio, DXU, OEMConfig	
Software Maintenance	Datalogic Shield: recurring security patches, firmware updates, and OS upgrades.	
Development	Java, Cordova and Xamarin SDK available	
MDM Compatibility	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche, 42Gears SureMDM, Microsoft Intune	
Terminal Emulation Compatibility	StayLinked SmartTE, Ivanti Velocity	
SYSTEM		
Expansion Slots	Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible	
SIM Slot	MicroSIM Standard size	
Memory	System RAM: 3 GB; eMMC Flash: 32 GB	
Microprocessor	2 GHz Octa-core	
Operating System	Android v9 with GMS (upgradeable to Android 10)	
Real-Time Clock	Time and date stamping under software control	
WARRANTY		
Warranty	1-Year Factory Warranty	

CESSOR Δ Stations/Charg Bas







94ACC0192

94A150095 Single Slot Dock

94A150096 Battery Charger 3-Slot Dock

Single Slot Ethernet Adaptor, also available in a 3-slot Adaptor

94A150097 Vehicle Dock

Miscellaneous

94ACC0201 Pistol Grip

94ACC0193 Rubber Boot

© 2018-2022 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates, * Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. * Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. * Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. * Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. * The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. * All other trademarks and brands are property of their respective owners * Product specifications are subject to change without notice. * DS-MEMOR10-EN Revision 1 2022/213