# **ZT400 Series Industrial Printers**



### A new level of performance, versatility and ease of use

Keep your critical operations running efficiently with Zebra's durable ZT400 Series printers. The ZT400 offers advanced technology that drives versatility, ease of use and performance to a new level. Available in three print resolutions and two print widths, the ZT400 Series addresses a broad array of applications throughout manufacturing, transportation and logistics, retail and more. See printer status at a glance and manage settings quickly using the large color touch display. Field-installable connectivity, media handling and RFID options let you easily add new features as your needs evolve. And your IT department will find ZT400 printers easy to integrate and manage, thanks to Zebra's Print DNA<sup>™</sup> suite of applications, utilities and developer tools–all powered by Link-OS<sup>®</sup>. The result? The ZT400 offers the versatility, reliability, and performance to meet your industrial printing needs—today and tomorrow.



#### Versatile to Meet Your Evolving Needs

#### **Configure Your Way With Multiple Connectivity Options**

The ZT400 comes standard with Ethernet, Serial, USB, dual USB Host and Bluetooth<sup>®</sup> 4.1. Add the optional dual-band wireless card with 802.11ac Wi-Fi and Bluetooth for blazing fast and reliable wireless connections.

#### Built to Handle a Wide Range of Media and Applications

You can count on the ZT400 to print a variety of different label formats on a variety of different media types. The printer is offered in both 4 in. and 6 in. models, with 203 dpi, 300 dpi and 600 dpi\* (600 dpi available on 4 in. ZT411 only). Add factory- or field-installable RFID technology to print and encode labels for greater tracking abilities and deeper visibility. Select Zebra's exclusive ZT411 RFID On-metal Tagging Solution, which is the only dedicated option for printing and encoding thicker RFID labels for metal containers and assets.

#### **Dual USB Host Ports For Added Flexibility**

Dual USB Host ports allow you to directly connect a wide range of USB device types. Use a memory stick to replicate firmware, files and configurations, or easily print and transfer formats. Simplify data entry by simultaneously connecting a scanner and keyboard—with two host ports, there's no need to plug and unplug peripherals.

#### **Designed to Evolve With Your Needs**

You can customize the ZT400 with a range of media handling options that can be installed in minutes. Two open media slots accommodate additional communication options. And, the robust processing power and memory can support firmware upgrades and new Print DNA tools for years to come.

#### **Effortless to Integrate and Operate**

#### Large Color Touch Display Makes Operation a Snap

It's easy to set up and use the ZT400 with its intuitive icon-based interface. The 4.3-inch full-color touch display allows you to quickly navigate printer settings with the user friendly icon menu system to change languages, printer settings, connectivity options and more. Zebra touchscreens are expertly designed and thoroughly tested with toughness and reliability consistent with the rest of the Zebra printer portfolio. This includes Zebra's robust tolerance to temperature, humidity, dust, and other environmental challenges. See color-coded

Keep your critical operations running efficiently. For more information, visit www.zebra.com/zt400 alerts from a distance when the printer is paused or in an error state, so you instantly know what the printer needs to stay up and running.

#### Easy Media and Ribbon Loading

The side-loading supplies path makes loading simpler, faster, and more intuitive. The color-coded media path guides you on how to thread the media and ribbon through the printer, while lighted paths make it easy to see, even in poorly lit environments.

#### **Space-Saving Design For an Easier Fit**

Constructed using a bi-fold door, these printers are designed to easily fit in space-constrained environments. ENERGY STAR<sup>®</sup> qualified, they save you money throughout their lifecycle.

#### **Direct Connection to Your Industrial Ethernet Network**

With the Network Connect option, you can connect ZT400 printers directly to your Industrial Ethernet network without any additional equipment. This eliminates vulnerability points, improves security and saves man-hours in setup, management and troubleshooting.

#### Pair Devices and Access Information at a Touch

With the Print Touch<sup>™</sup> app, you can pair ZT400 Series printers to NFC-enabled devices with a simple tap. Dynamic QR codes give you immediate access to the data you need, including Zebra how-to videos and product support.

#### **Easy to Manage**

#### Zebra Print DNA—Transforming Printers From the Inside

The printer hardware is just the start of what you need to maximize the value of your printers. The ZT400 is powered by Link-OS, Zebra's robust printer operating system, and Print DNA, a combination of productivity, management, development and visibility tools. The result is a superior printing experience through better performance, simplified remote manageability and easier integration.

#### Easily Manage All Your Printers—All From a Single Location

With our comprehensive and flexible remote management tools, you can maintain, secure and troubleshoot printers simply and easily, from anywhere, at anytime. With Printer Profile Manager Enterprise, a Print DNA option, you can manage one printer, a group of specific printers or all your printers anywhere in the world. This browser-based solution lets you instantly discover every Link-OS printer on your network—there's no need to manually track down, configure, or troubleshoot printers. In addition to optional enterprise remote management tools, we offer a full suite of complimentary deployment utilities to simplify initial setup and configuration.

#### Seamless Integration With Your Device Management System

Get the simplicity of a single pane of glass to manage all of your Zebra devices and printers—including the ZT400 Series. With Print DNA's MDM Connectors, you can easily integrate networked ZT400 Series printers into your existing AirWatch or SOTI MobiControl device management system.

#### Performance You Can Count On

#### **Maximum Throughput and Productivity**

Avoid slowdowns to your operations and processes while waiting for a label to print. Best-in-class performance provides fast first label out and high throughput to make sure the label is ready when you need it.

#### **Rugged Durability For Demanding Applications**

You can count on the ZT400 Series to serve your business for years. Its durable metal frame holds up in the most demanding environments, while a long life coating protects the printheads when printing in direct thermal mode, reducing the need to replace printheads. Ensure optimal print quality with the printhead element out detection feature. Every detail has been carefully designed and tested to deliver maximum uptime over the printer's life—from the carbon fiber reinforcing the gears to a high retention USB cable.

#### **Consistently Exceptional Zebra Certified Supplies**

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce, and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimized performance in your Zebra printer—and peace of mind for you. For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies.

### Maximize Uptime, Business Operations and Printer Visibility With Services

You invest in Zebra printers to boost the efficiency of your critical operations. Now, you can ensure predictable performance and eliminate unbudgeted repair expenses with Zebra OneCare. You get unmatched technical support direct from Zebra, as well as comprehensive repair services, including accidental damage and defined repair turn-around times. And, Zebra's Support and Visibility Services provide the real-time insight into printer operational information you need to increase printer availability and optimize utilization within your workflows.

## **Specifications**

#### **Standard Features**

- Print Methods: Thermal transfer and direct thermal printing
- Construction: Metal frame and bi-fold metal media cover with enlarged clear viewing window
- Side-loading supplies path for simplified media and ribbon loading
- Thin film printhead with E<sup>3™</sup> Element Energy<sup>™</sup> Equalizer for superior print quality Communications: USB 2.0, high-speed, RS-232 Serial, 10/100 Ethernet,
- Bluetooth 4.1, Dual USB Host • 4.3-inch color touch display with intuitive menu for quick operation and settings
- management
- · Bi-colored status LEDs for quick printer status
- ENERGY STAR qualified
- · Zebra Designer Essentials: easy label design tool free at www.zebra.com/ zebradesigner

#### **Physical Characteristics**

····	
Dimensions (closed)	ZT411: 19.5 in. L x 10.6 in. W x 12.75 in. H 495 mm L x 269 mm W x 324 mm H
	ZT421: 19.5 in. L x 13.25 in. W x 12.75 H 495 mm L x 336 mm W x 324 mm H
	Note: Dimensions are for the base model printer. Consult your sales representative for specifics regarding other configurations.
Weight	ZT411: 36 lbs./16.33 kg ZT421: 40 lbs./18.14 kg
Printer Specifications	
Resolution	203 dpi/8 dots per mm 300 dpi/12 dots per mm (optional)

	600 dpi/24 dots per mm (optional for ZT411 only)
Memory	256 MB SDRAM memory 512 MB on-board linear Flash memory
Maximum Print Width	ZT411: 4.09 in./104 mm ZT421: 6.6 in./168 mm
Maximum Print Speed	ZT411: 14 ips/356 mm per second ZT421: 12 ips/305 mm per second
Media Sensors	Adjustable dual media sensors: transmissive and reflective
Print Length	ZT411 • 203 dpi: 157 in./3988 mm • 300 dpi: 73 in./1854 mm • 600 dpi: 39 in./991 mm ZT421 • 203 dpi: 102 in./2591 mm • 300 dpi: 45 in./1143 mm

#### **Media Characteristics**

Maximum Media Width	ZT411 • 1.00 in./25.4 mm to 4.5 in./114 mm tear/cutter • 1.00 in./25.4 mm to 4.25 in./108 mm peel/rewind ZT421 • 2.00 in./51 mm to 7.0 in./178 mm tear/cutter • 2.00 in./51 mm to 6.75 in./171 mm peel/rewind
Maximum Media Roll Size	8.0 in./203 mm O.D. on a 3 in./76 mm I.D. core
Thickness	0.0023 in./0.058 mm to 0.010 in./0.25 mm
Media Types	Continuous, die-cut, notch, black-mark
Ribbon Characteristics	
Standard Length	1476 ft./450 M

etanaara zengtii	
Width	ZT411: 2.00 in./51 mm to 4.33 in./110 mm ZT421: 2.00 in./51 mm to 6.85 in./174 mm
Core	1.0 in./25 mm I.D.

#### Environmental

Environmental	
Operating Temperature	Thermal transfer: 40° F to 104° F/5° C to 40° C Direct thermal: 32° F to 104° F/0° C to 40° C
Storage/ Transportation Temperature	-40° F to 140° F/-40° C to 60° C
Operating Humidity	20% to 85% non-condensing
Storage Humidity	5% to 85% non-condensing
Firmware	

ZBI 2.0<sup>™</sup>—Optional powerful programming language that lets printers run standalone applications, connect to peripherals, and much more. ZPL and ZPL II®—Zebra Programming Language provides sophisticated label formatting and printer control and is compatible with all Zebra printers. EPL and EPL2<sup>™</sup>— Eltron<sup>®</sup> Programming Language with Line Mode simplifies label formatting and enables format compatibility with legacy applications. (EPL available on 203 dpi models only.)

#### Electrical

Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz, ENERGY STAR qualified

#### . . Opti

Options and Accessories	
Communication	Two open communication slots to add internal cards for: • Dual band 802.11ac Wi-Fi and Bluetooth • Parallel (bi-directional interface) • 10/100 Ethernet • Applicator interface
Media Handling	<ul> <li>Rewind: Internally rewinds a full roll of printed labels on 3 in. core, or peels and rewinds liner (factory installed only)</li> <li>Peel: Front-mount, passive peel option</li> <li>Peel: Liner take-up—additional full-roll liner take-up spindle accommodates standard printer base</li> <li>Cutter: Front-mount guillotine cutter and catch tray</li> <li>1 in. I.D. Core media supply hanger (ZT411 only)</li> <li>Ink-side in ribbon supply (ZT411 only)</li> </ul>
RFID	<ul> <li>Supports tags compatible with: UHF EPC Gen 2 V2.1, ISO/IEC 18000-63 and RAIN RFID protocols</li> <li>Integrated RFID system is user-upgradable in the field and available on both 4 in. and 6 in. models</li> <li>Adaptive Encoding Technology automatically selects optimum encode settings</li> <li>Field installable on-metal RFID kit available*</li> <li>*ZT411 only (not available on the 600 dpi model)</li> </ul>
Keyboard Display Unit	ZKDU <sup>™</sup> keyboard display units for stand-alone printing applications
Fonts and Graphics	

16 resident expandable ZPL II bitmap and two resident scalable ZPL fonts

Asian and other international scalable and smooth bitmapped fonts

Unicode<sup>™</sup>: For multi-language printing

Downloadable objects include graphics, scalable and bitmap fonts, label templates and formats

IBM Code Page 850 international character sets are available in the fonts A, B, C,

D, E, F, G and O through software control Code Page 1250, 1252, 1253, 1254, 1255 Support with font 0

64 MB user-available non-volatile memory storage for downloadable objects 8 MB user-available SDRAM

#### **Markets and Applications**

#### Manufacturing

- · Work-in-process Product ID/
- serial numbers
- Package labeling · Receiving/put-

### away labeling Transportation

- and Logistics Order picking/ packing
- Shipping/receiving
- Cross-docking
- Compliance labeling

#### Retail

- Distribution centers
- Back-of-store operations

#### Healthcare

- Laboratory labeling
- Blood bank labeling
- Asset tracking
- Pharmacy labeling

## **Specifications**

Barcode Symbologies	
Linear Barcodes	Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2- or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code
Two Dimensional Barcodes	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, TLC 39, MicroPDF, RSS-14 (and composite), Aztec
Agency Approvals	
Safety and EMC	IEC 62368, Class B, EN 55032, EN 55035, EN 61000- 3-2, EN 61000-3-3
Product Markings	Including, not limited to, cTUVus, CE, FCC, ICES- 003(B), VCCI, RCM, NOM, S-Mark, CCC, EAC, BSMI, KCC, SABS, In-Metro, BIS.
Print DNA Software	e Solutions
Development Tools	With faster, easier and smarter integration of Zebra printers with your devices and applications, your Zebra printing solutions are up and running in less time, with less cost.
Management Tools	Minimize IT effort and maximize IT control with Print DNA management tools—the easy way to add and manage any number of printers, anywhere—from a handful of printers to thousands of printers all around the world.
Productivity Tools	Reach new levels of productivity with innovations that streamline tasks and workflows, optimize device performance and solve tomorrow's printing problems today.
Visibility Tools	Regardless of whether or not you have an existing Mobile Device Management solution in place, robust visibility tools provide unparalleled insight into printer health, usage and performance.

#### **Recommended Services**

Zebra OneCare Essential and Select Services maximize the availability and productivity of your devices. Key features include 24/7 technical support, comprehensive coverage, advance replacement and software updates. Optional Support and Visibility Services are available. For more information go to www.zebra.com/zebraonecare. (Note: Service availability may vary by region.)

#### Print DNA Software

This printer is supported by our powerful Print DNA suite of applications, utilities and developer tools that give our printers better performance, simplified remote manageability, and easier integration. Print DNA features may vary by model and a Support Contract may be required. For more information, please visit: www.zebra.com/printdna

Features are subject to availability. Specifications are subject to change without notice.



NA and Corporate Headquarters +1 800 423 0442 inquiry4@zebra.com

Asia-Pacific Headquarters +65 6858 0722 contact.apac@zebra.com EMEA Headquarters zebra.com/locations contact.emea@zebra.com Latin America Headquarters zebra.com/locations la.contactme@zebra.com

ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corporation, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. ©2023 Zebra Technologies Corporation and/or its affiliates. All rights reserved. 09/15/2023. Part number: SS-ZT400-SERIES